



ŘEZNÉ KOTOUČE SUN-disc M

...vhodné pro ocel i nerez materiály

SUN-disc M	115-2	125-2	230-2
			
Objednací číslo	909 866	909 867	909 869
Max. otáčky	13 300	12 200	6 600
fx síla x otvor	115 x 2 x 22	125 x 2 x 22	230 x 2 x 22
	35	35	35

ŘEZNÉ KOTOUČE TURBO DISC

...vhodné pro řezání nerezových trubek a plechů

TURBO DISC	50-1	75-1	115-1	125-1	150-1,6	178-1,6
						
Objednací číslo	908 074	908 078	908 075	908 076	909 648	908 440
Max. otáčky	30 000	20 200	13 300	12 200	10 200	8 600
fx síla x otvor	50 x 1,2 x 6	75 x 1,2 x 10	115 x 1,2 x 22	125 x 1,2 x 22	150x1,6x22	178x1,6x22
	50	50	25	25	25	25



ŘEZNÉ KOTOUČE TAF s příměsí CE

NOVINKA

TAF	115-1	125-1	125-1,6
			
Objednací číslo	07147	07547	07549
Max. otáčky	13 300	12 200	12 200
fx síla x otvor	115 x 1 x 22	125 x 1 x 22	125 x 1,6 x 22
	25	25	25



ŘEZNÉ KOTOUČE 3M

3M typ T41	115-1	125-1	125-1,6	150-1,6
				
Objednací číslo	07143	07543	07545	07677
Max. otáčky	13 300	12 200	12 200	10 200
fx síla x otvor	115 x 1 x 22	125 x 1 x 22	125 x 1,6 x 22	150 x 1,6 x 22
	25	25	25	25

Na jaký typ brusky upnout tyto řezné kotouče?

Průměr kotouče 125 = UWG 10-R

Průměr 125 a 150 = UWG 10-R a UWK 10-R